



71915 ACE/HCP4A Bearing 2D drawings and 3D CAD models

75 mm x 105 mm x 16 mm SKF 71915 ACE/HCP4A angular contact ball bearings

Bearing No. 71915 ACE/HCP4A

| | |
|---|--------------|
| Size | 105x75x16 mm |
| Bore Diameter | 105 mm |
| Outer Diameter | 75 mm |
| Width | 16 mm |
| d | 75 mm |
| D | 105 mm |
| B | 16 mm |
| d ₁ | 84.3 mm |
| d ₂ | 81.8 mm |
| D ₁ | 95.52 mm |
| r _{1,2} - min. | 1 mm |
| r _{3,4} - min. | 0.3 mm |
| a | 30.2 mm |
| d _a - min. | 79.6 mm |
| d _b - min. | 77 mm |
| D _a - max. | 100.4 mm |
| D _b - max. | 103 mm |
| r _a - max. | 1 mm |
| r _b - max. | 0.3 mm |
| d _n | 86.5 mm |
| Basic dynamic load rating - C | 21.2 kN |
| Basic static load rating - C ₀ | 16.3 kN |
| Fatigue load limit - P _u | 0.68 kN |
| Limiting speed for grease | 18500 r/min |



NTN BEARING USA CORP.

| | |
|------------------------------------|---------------------|
| Lubrication | |
| Limiting speed for oil lubrication | 29000 mm/min |
| Ball - D_w | 9.525 mm |
| Ball - z | 23 |
| G_{ref} | 4.5 cm ³ |
| Calculation factor - e | 0.68 |
| Calculation factor - Y_2 | 0.87 |
| Calculation factor - Y_0 | 0.38 |
| Calculation factor - X_2 | 0.41 |
| Calculation factor - Y_1 | 0.92 |
| Calculation factor - Y_2 | 1.41 |
| Calculation factor - Y_0 | 0.76 |
| Calculation factor - X_2 | 0.67 |
| Preload class A - G_A | 192 N |
| Preload class B - G_B | 577 N |
| Preload class C - G_C | 1150 N |
| Calculation factor - f | 1.16 |
| Calculation factor - f_1 | 0.98 |
| Calculation factor - f_{2A} | 1 |
| Calculation factor - f_{2B} | 1.04 |
| Calculation factor - f_{2C} | 1.08 |
| Calculation factor - f_{HC} | 1.01 |
| Preload class A | 152 N/micron |
| Preload class B | 228 N/micron |
| Preload class C | 299 N/micron |
| d_1 | 84.3 mm |
| d_2 | 81.8 mm |
| D_1 | 95.52 mm |
| $r_{1,2}$ min. | 1 mm |



NTN BEARING USA CORP.

| | |
|--|---------------------|
| $r_{3,4}$ min. | 0.3 mm |
| d_a min. | 79.6 mm |
| d_b min. | 77 mm |
| D_a max. | 100.4 mm |
| D_b max. | 103 mm |
| r_a max. | 1 mm |
| r_b max. | 0.3 mm |
| d_n | 86.5 mm |
| Basic dynamic load rating C | 21.2 kN |
| Basic static load rating C_0 | 16.3 kN |
| Fatigue load limit P_u | 0.68 kN |
| Attainable speed for grease lubrication | 18500 r/min |
| Attainable speed for oil-air lubrication | 29000 r/min |
| Ball diameter D_w | 9.525 mm |
| Number of balls z | 23 |
| Reference grease quantity G_{ref} | 4.5 cm ³ |
| Preload class A G_A | 192 N |
| Static axial stiffness, preload class A | 152 N/ μ m |
| Preload class B G_B | 577 N |
| Static axial stiffness, preload class B | 228 N/ μ m |
| Preload class C G_C | 1150 N |
| Static axial stiffness, preload class C | 299 N/ μ m |
| Calculation factor f | 1.16 |
| Calculation factor f_1 | 0.98 |
| Calculation factor f_{2A} | 1 |
| Calculation factor f_{2B} | 1.04 |
| Calculation factor f_{2C} | 1.08 |
| Calculation factor f_{HC} | 1.01 |



NTN BEARING USA CORP.

| | |
|---|---------|
| Calculation factor e | 0.68 |
| Calculation factor (single, tandem) Y_2 | 0.87 |
| Calculation factor (single, tandem) Y_0 | 0.38 |
| Calculation factor (single, tandem) X_2 | 0.41 |
| Calculation factor (back-to-back, face-to-face) Y_1 | 0.92 |
| Calculation factor (back-to-back, face-to-face) Y_2 | 1.41 |
| Calculation factor (back-to-back, face-to-face) Y_0 | 0.76 |
| Calculation factor (back-to-back, face-to-face) X_2 | 0.67 |
| Mass bearing | 0.29 kg |